

FEATURES

- Larger field of view & superior depth of focus
- Lighter & Smaller Telescopes
- Clear & Bright vision over the full field
- No Distortion & No Fatigue
- KEPLERIAN (Prismatic) Type (which the prism is contained) provides high resolution : Looks3200, Looks3500, Looks5000
- Frames
 - Frames of hypoallergenic pure titanium & goggle frames
 - Ergonomic & Stylish titanium frame with plastic temples
 - Comfortable sport goggle frames
- Colorful frame options

Front part



Rear part



Front / Rear



SPECIFICATIONS

Model	Mag.	F.O.V. @40cm	Weight*
Looks2500	2.5x	160 mm @ 40 cm	PA 27.0g
			HT 41.0g
Looks2500L	2.5x	150 mm @ 40 cm	PA 21.5g
			HT 35.5g
Looks2800	2.8x	130 mm @ 40 cm	PA 26.0g
			HT 40.0g
Looks3200	3.2x	86 mm @ 40 cm	PA 45.0g
			HT 56.6g
Looks3500	3.5x	98 mm @ 40 cm	PA 62.0g
			HT 75.5g
Looks5000	5.0x	62 mm @ 40 cm	PA 79.0g
			HT 83.0g
Looks7500	7.5x	41 mm @ 40 cm	PA 80.2g
			HT 84.5g
Flip-up	Magnification : 2.5x Working Distance : 30cm, 36cm, 42cm, 48cm		

* Weight based on TTL loupe with plano lens

Looks 2500



Looks2800



Looks3200



Looks3500



Looks5000



Looks7500



Flip-up 2.5x

Authorised Distributors :
JOLLY TECHNOCRATS

An ISO 9001:2015 Company

Complete Range of : OT Equipment, Skin, Surgery & Gynae Products

304, Mansarovar Building, 90, Nehru Place, New Delhi-110019, (INDIA)

Phone : + 91-11-46066071, Telefax : + 91-11-46066072, e-mail : jollytechnocrats@gmail.com, jollytechnocratsservice@gmail.com

website : www.jollytechnocrats.in, Mobile : +91-9810025581, +91-9650595509



L²S15 LED LIGHT SYSTEM - L²S15



Specifications

Operating Power	DC3.7V --- 800mA
Operating Time	About 23 hrs. (1 st step mode: Minimum intensity)
	About 11 hrs. (2 nd step mode)
	About 8 hrs. (3 rd step mode)
	About 5 hrs. (4 th step mode: Maximum intensity)
Charging Time (Full charge)	5 hours

LED Illumination

Brightness (lx) @WD400mm	Type	LLM1582	LLM1574	LLM1566
	1 st step		12,000	13,000
2 nd step		22,000	24,000	32,000
3 rd step		30,000	32,000	44,000
4 th step		39,000	43,000	59,000
Field of View Size (mm) @WD400mm		82	74	66
Weight (g)		35.1	32.8	34.2
Color Temperature, Wavelength Range		6000 K, 400 ~ 700nm (Visible Ray)		
Uniformity		More than 80% @WD400mm		
LED Operating Power		DC3.0V --- 0.7A		
LED Lifetime (Guaranteed Time)		50,000 hours		

L²SW Wireless Headlight with uniform & Clear vision



FEATURES

- Wireless Headlight with uniform & Clear vision
- Weight only 26.5 g with small battery
- Battery running time maximum 8 hours 30 minutes (at the lowest level with Large size battery)
- 4 pcs Complimentary Battery packs provided (2 large, 2 small size)

B. LED Illumination

Brightness (lx) [±2000 lx] @ WD400mm	Type	LLMW
	1st step	
2nd step		10,000
3rd step		15,500
Field of View (mm) @WD400mm		Ø 82mm
Color Temperature, Wavelength Range		6000 K, 400 ~ 700 nm(Visible)
Uniformity		More than 80% @WD400mm
LED Life Span (Guaranteed Time)		50,000 hours

XDLight LED Light System - XD Light



Specifications

Operating Power	DC3.7V --- 550mA
Operating Time	About 22 hours. (1 st step mode: Minimum)
	About 11 hours. (2 nd step mode)
	About 7.5 hours. (3 rd step mode)
	About 5.5 hours (4 th step mode: Maximum)
Charging Time (Full charge)	About 4 hours

LED Illumination

Brightness (lx) [±2000 lx] @WD400mm	1 st step	9,000
	2 nd step	16,000
3 rd step	23,000	
4 th step	29,000	
Field of View Size (mm) @WD400mm		82
Weight (g)		
Color Temperature, Wavelength Range		6000 K, 400 ~ 700nm (Visible Ray)
Uniformity		More than 80% @WD400mm
LED Operating Power		DC3.0V --- 500mA
LED Life Span (Guaranteed Time)		50,000 hours

L²S PORTABLE LED LIGHT SYSTEM - L²S14C



- Wireless
- Included extra battery pack

LED Illumination

Color Temperature, Wavelength Range	6000 K, 400 ~ 700nm (Visible Ray)
Field of View / Brightness, Uniformity (LLM14XX)	Ø 82mm/22,000 lx, 60% @WD400mm Ø 74mm/25,000 lx, 60% @WD400mm Ø 66mm/32,000 lx, 60% @WD400mm
LED Operating Power	DC3.0V --- 500mA
LED Life Span (Guaranteed Time)	50,000 hours @70% of Maximum level

